MODEL #409 (ORIGINAL) INSTALLATION INSTRUCTIONS

TAKE-A-TICKET, INC. RECOMMENDS YOU HAVE A PROFESSIONAL CONTRACTOR INSTALL THIS UNIT. HERE ARE SUGGESTIONS IF YOU CHOSE TO DO IT YOURSELF.

Note: You may want to remove the loose top glass that is taped in before you start or leave it taped in and work carefully.

#5 STEPS FOR INSTALLATION:

- 1. Before you cut a hole make sure you have clearance under the counter!
 - The hole is at least $14-3/4" \times 18-3/4"$ and the depth of the unit below the counter is about 15".
 - NOTE: The 18-3/4" measurement is from customer to clerk, across the counter.
 - The hole should be set in at least 3" from the clerk's side of the counter so the clerks won't bump into anything extending from under the counter.
 - MAKE SURE YOU HAVE CLEARANCE!!! This unit hangs down about 15" from counter to the bottom of the unit.
 - Once you are sure of clearance and the hole's location check it again, and again!
- 2. Cut the hole. Wait! Are you sure about the location?
 - The hole size is 14-3/4" (right to left) \times 18-3/4" (customer to clerk).
 - · Apply a bead of caulking around the hole on the counter surface.
 - Drop the upper portion of the dispenser with the metal frame and glass into hole. The open side with no white plastic faces the clerk's side.
- 3. Separate the upper and lower portions of the dispenser. Do not lose the carriage bolts, washers and wingnuts. Remove the trays from the unit and set aside.
 - Apply a bead of caulking around the hole on the counter surface.
 - Drop the upper portion of the dispenser with the metal frame and glass into hole.
 The open side with no white plastic faces the clerk's side.
- 4. Reattach the base of the dispenser to the upper part using bolts, washers, and nuts. There is some adjustment possible up and down for the lower unit.
- 5. Load the trays and place them in the dispenser.

Note: The bottom piece of glass is sealed in place to prevent leaks under the counter. Questions? Call us at (800) 253-4295

OPERATION OF ALL #416 ORIGINAL DISPENSERS

- Hold ticket pack on both ends and flex up and down. This will allow much easier dispensing
- 2. Lay ticket pack in tray under the plastic rods
- 3. **DO NOT** feed the tickets over the rods
- 4. Bottom glass is sealed in to prevent leaking under the counter
- 5. Top glass is loose to allow cleaning and replacement. The suction cup provided should be used top remove the glass as soon after a spill as possible. Removal after the liquid has dried is much more difficult.

Questions? Call Take-A-Ticket at (800) 253-4295 or fax: (541) 967-8415